

SPECIFICATIONS: Sludge Treat

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



SLUDGE TREAT Fuel Oil System Cleaner

Date: August 2017

Storage tank additive which cleans and conditions heating system fuel oil. **Sludge Treat** helps prevent fuel related heating system failures, improves combustion efficiency, reduces soot formation and conserves energy by reducing fuel oil waste.

Prevents troublesome fuel oil waxing and gelling. Disperses condensate water to aid in resistance to fuel tank corrosion, sludge formation and winter freeze-ups. Regular use of **Sludge Treat** helps avoid water-blocked filters while cleaning strainers, nozzles, pumps and burners, and minimizing burner breakdown. Application of **Sludge Treat** helps prevent sludge build-up and ice formation in fuel lines assuring a steady flow at all times. Easy to use. Pour directly into fuel tank at time of oil delivery for year round, summer storage and heating season protection. One quart treats approximately 500 gallons. For "One-Shot" applications to standard 275 gallon capacity tanks, use **Hercules Power Flow™** (similar product in a convenient, 16-ounce container).



APPROVALS & LISTINGS

Not applicable.

SPECIFIC USES

Use to disperse sludge and water, prevent icing, improve combustion and conserve energy by reducing fuel waste. Cleans clogged lines, strainers, pumps, burners and nozzles due to sludge and water build up.

SPECIFIC APPLICATIONS*

Use in fuel oil systems and storage tanks.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
35310	1 qt.	12	26.2 lbs.