

## DIRECTIONS FOR USE

Just before delivery of oil, pour **Sludge Treat** into oil fill inlet. Receiving oil delivery provides the agitation that helps **Sludge Treat** disperse water and sludge. **Sludge Treat** can also be added to a full tank, but product action will progress at a slower rate. Several applications of **Sludge Treat** may be required to completely clear existing accumulations of sludge or water in the tank. Suggested usage amounts are recommended to help prevent sludge build-up in new or clean tanks.

For initial dosage, use one pint for each 275 gallons of tank capacity. Use two quarts for a 1000-gallon tank. For follow-up dosages, the quantity table below is a guide.

Amounts	
Type Fuel Oil	Per 1000 Gals. Oil
No. 2	1 Quart
No. 3	1 Quart
No. 5	1 Quart
No. 6	2 Quarts

## PHYSICAL PROPERTIES

Specific gravity:	.8
Solubility in water:	Forms an emulsion
Solubility in oil:	Fully soluble
Boiling point:	317-388° F
Vapor pressure:	at 100°F 0.1
Appearance/color/odor:	Light brown color. Hydrocarbon odor

## WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using this product.
- **Keep out of reach of children.**
- Avoid contact with eyes and skin.
- Harmful or fatal if swallowed. Contains mineral spirits.
- Avoid breathing vapor, mist, or fumes. Use with adequate ventilation.
- Prolonged exposure to vapors may cause headaches or dizziness.
- Prolonged or repeated skin contact may cause irritation.
- Wash thoroughly after handling.

## MATERIAL SAFETY INFORMATION

### FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7331E

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of <a href="http://www.Oatey.com">www.Oatey.com</a>

**HMIS® ratings** Health: 2  
 Flammability: 2  
 Physical hazard: 0