

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



PURPLE PRIMER FOR PVC & CPVC

Date: August 2017

- Professional grade purple primer for use on all schedules and classes of CPVC and PVC pipe and fittings.
- Lo-V.O.C. Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements.
- Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.
- Purple Tint ensures piping has been primed prior to solvent cement application.
- Meets ASTM F656.



APPROVALS & LISTINGS



Complies with NSF/ANSI 61 health effects requirements.

PW-DWV-SW

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7402E

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of www.oatey.com

HMIS® ratings Health: 2
 Flammability: 3
 Physical hazard: 0

SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
60403	4 oz.	24	8 lbs.
60413	8 oz.	24	14 lbs.
60415	16 oz.	12	14 lbs.
60420	32 oz.	12	26 lbs.
60425	Gallon	6	49 lbs.

PHYSICAL PROPERTIES

Appearance: Purple Liquid